


T/5x



SUGGESTED RETAIL: \$699.00

No model in REL's long history has sold more units nor engendered more affection than our T/5. Here reimagined in a modern, elegant, new form factor, T/5x's mission remains the same: make remarkable bass far beyond its modest size, do so in a way that complements every interior's style, and eliminate all visual distraction. Mission Accomplished.

Specifications

TYPE	Closed Box, down-firing driver
ACTIVE DRIVER SIZE & MATERIAL	8 in. FibreAlloy™, 200mm long-throw, inverted alloy dust cap, steel chassis
PASSIVE RADIATOR SIZE & MATERIAL	N/A
LOW FREQUENCY EXTENSION	-6dB at 32 Hz
INPUT CONNECTORS	High Level Neutrik Speakon, Low Level single RCA, LFE RCA
OUTPUT CONNECTORS	N/A
POWER OUTPUT	125 watts (RMS)
AMPLIFIER TYPE	Class A/B
WIRELESS CAPABILITY	Arrow (Optional), Zero Compression, Single Large Scale Integrated Chip
DUAL PARAMETRIC FILTER	N/A

Protection System

FULLY ELECTRONIC SET SAFE	Yes
D.C. FAULT	Yes
OUTPUT SHORT	Yes
MAINS INPUT VOLTAGE	220-240 volts, 110-120 volts for certain markets
FUSES	1.6 Amp semi delay 230 volts operation, 3.15 Amp semi delay 115 volts operation

Dimensions

W X H X D	11.8 x 12 x 12.3 in., (300 x 307 x 313 mm)
NET WEIGHT	31.5 lbs. (14.3 kg)
FINISH	High Gloss Black, High Gloss White, 5 coats

Supplied Accessories

MAINS LEAD	Yes
NEUTRIK SPEAKON	Yes (10 Meters Nominal)
INTERCONNECT	
USERS MANUAL	Yes

